

Tubería acero al carbón **ASTM A500/A513 GR.B** Redondo Con costura

Diametro Nominal		Diametro Exterior		Espesor de Pared				Peso Nominal	
Pulg.	mm	Pulg.	mm	Pulg.	mm	Cal.	Ced.	Kg./Mts.	Lb/Pie
1/2"	12.70	0.840	21.34	0.075	1.90	14	30	0.95	0.64
				0.105	2.66	12	40	1.27	0.85
3/4"	19.05	1.050	26.67	0.075	1.90	14	30	1.21	0.81
				0.105	2.66	12	40	1.63	1.09
1"	25.40	1.315	33.40	0.075	1.90	14	30	1.53	1.03
				0.135	3.42	10	40	2.53	1.70
1 1/4"	31.75	1.660	42.16	0.090	2.28	13	30	2.25	1.51
				0.135	3.42	10	40	3.27	2.20
1 1/2"	38.10	1.900	48.26	0.090	2.28	13	30	2.59	1.74
				0.135	3.42	10	40	3.79	2.54
2"	50.80	2.375	60.33	0.105	2.66	12	30	3.93	2.64
				0.135	3.42	10	40	4.81	3.23
2 1/2"	63.50	2.875	73.03	0.105	2.66	12	30	4.79	3.22
				0.188	4.76	3/16	40	8.03	5.39
3"	76.20	3.500	88.90	0.120	3.04	11	30	6.45	4.33
				0.224	5.69	4	40	11.67	7.83
4"	101.60	4.500	114.30	0.120	3.04	11	30	8.35	5.61
				0.224	5.69	4	40	15.24	10.23
6"	152.4	6.625	168.28	0.188	4.76	3/16	30	19.23	12.91
				0.280	7.11	0.280	40	28.24	18.96